

PRODUCT DATA

Date: November 2005

Code: 03596/25

IDENDEN T303 SELF-ADHESIVE BRIGHT FOIL TAPE

Idenden T303 Self-Adhesive Bright Foil Tape is the market leading product for the heating, ventilation and air conditioning and asbestos abatement sectors. The high standards of reliability, strength and durability mean it is now used for diverse applications in many other sectors, for example process plant, marine and offshore. Idenden T303 is manufactured to the highest specifications and is coated with a high tack rubber/resin adhesive system and protected by a removable release paper. Idenden T303 is the first choice of contractors and specifiers and is ideal for most HVAC applications. Idenden T303 provides unrivalled performance, maintaining insulation efficiency by protecting against the effects of fire, moisture and dust. It is easy to apply, exhibiting instant adhesion and can be moulded to any profile. The final bond has high shear strength and the foil promotes the optimum balance of surface conformity and tensile strength. This makes it ideal for lap sealing foil faced insulation materials, metal and duct sealing, asbestos abatement tenting and other general purpose applications.

Features

- High standards of reliability, strength and durability
- High tack adhesive
- Consistent performance over a wide temperature range
- Class 0 compliance

Product Characteristics

Finish	Bright aluminium foil
Adhesive	Rubber/resin
Release paper	High quality siliconised paper
Packaging	Cartons of 24 x 50mm rolls of 45m length, 16 x 75mm rolls of 45m length and 12 x 100mm rolls of 45m length
Shelf life/storage	At least 12 months from date of manufacture when stored in a dry place within the temperature range +10°C to +30°C.

Typical Performance Data (approx.)

Service temperature	-10°C to +90°C
Application temperature	-5°C (minimum)
Reaction to fire	Class 0 compliance: Independently tested to BS 476 Part 6 and Part 7 – Class 1
Ultimate tensile strength (approx.)	89 N/25mm
Elongation (approx.)	8-11%

Peel adhesion to steel (approx.)

Initial: 20-25 N/25mm
24 hours: 25-30 N/25mm

Water vapour

ASTM B479 95 0.015 g/m²

Directions for use

IMPORTANT

Before embarking on any work involving Idenden T303 Self-Adhesive Bright Foil Tape, the separate Safety Data Sheet should be carefully studied by those carrying out the work.

1. Surfaces to be bonded must be clean, dry and free from dust, grease, oil and loose materials. If necessary, wipe surfaces sparingly with a cloth dampened with a ketone-free cleaner such as Evo-Stik Cleaner 4 and allow to dry for at least an hour before tape application.
2. The butt joints of insulation sections should be positioned together without gaps to ensure an adequate bond.
3. Select a tape width suitable for the application. A width of 50 mm is suitable for closely positioned, flat sections. Otherwise, select a tape the thickness of the insulation plus 50 mm to allow for the exposed cut edge.
4. Remove the release paper from a section of the tape, taking care not to touch the adhesive surface. Align the tape centrally over the joint. Pull the tape taut and then press down well over the entire joint area. Rub the tape to remove any wrinkles or folds.

NOTE: Idenden T303 Self-Adhesive Bright Foil Tape is intended for joint sealing applications only, and is therefore not suitable for use where the joint is subject to mechanical stress. In this instance, insulation should be fixed using a suitable adhesive or hanger system.

Precautions in Use

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate health and safety data sheet for Idenden T303 Self-Adhesive Bright Foil Tape.

This Product Data Sheet covers just one of a large range of products supplied by Bostik Limited. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This Product Data Sheet supersedes all previous technical information on this product, and users of it are cautioned to ensure that it is the current issue. Destroy all previous Product Data Sheets, and if any doubt, contact Bostik Limited, quoting the code number in the top right hand corner on the front of this document. This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.

Bostik Limited, Common Road, Stafford, ST16 3EH, England

Tel: +44 (0)1785 272727

Fax: +44 (0)1785 257898

www.bostik.co.uk